

Specification Sheet

BWC Part Number#: 4420PL

Description: 22AWG 3 conductors 7 strands bare copper wire, plenum rated PVC insulation, shielded, and an overall plenum rated PVC jacket

1. Conductor

- 1.1. AWG Size & Stranding: 22 AWG 7 Strands Class B
- 1.2. Material: Annealed Bare Copper
- 1.3. Conductor Count: 3 Conductors

2. Insulation

- 2.1. Material: Plenum Rated Polyvinylchloride
- 2.2. Wall Thickness: 0.007"
- 2.3. Color Code: Black, Red, White

3. Assembly

- 3.1. Nominal Lay Length: 3.00" LHL (4.00 tw/ft)
- 3.2. Shield: Aluminum/Mylar Tape - 100% Coverage
- 3.3. Drain Wire: 24 AWG 7 Strands Tinned Copper


4. Jacket

- 4.1. Material: Plenum Rated Polyvinylchloride
- 4.2. Wall Thickness: 0.015"
- 4.3. Diameter: 0.122" \pm 0.010"
- 4.4. Color: Natural
- 4.5. Ripcord: Yes
- 4.6. Weight: 13 Lbs/Mft

5. Markings

- 5.1. Type: Cable permanently identified via surface inkjet print
- 5.2. Legend: LAKE CABLE E171202 22AWG 3C 75C (UL) CL3P OR FPLP OR C(UL)US CMP FT6
"ROHS COMPLIANT" MADE IN USA
- 5.3. Footage Markers: Yes (Ascending/Descending)

6. Standards

- 6.1. Cable suitable for installation under NEC (NFPA 70) articles 800, 725 and 760 guidelines
- 6.2. Cable suitable for installation in Canada under Section 60 of CEC, Part I
- 6.3. C(UL)US listed as CMP per UL standard 444 and per CSA C22.2 No. 214-17
- 6.4. UL listed as CL3P per UL standard 13 or FPLP per UL standard 1424
- 6.5. Cable meets NFPA 262 (Steiner tunnel) flame test
- 6.6. Cable meets RoHS 2002/95/EC Directive, RoHS 3 2011/65/EU Directive, RoHS 2015/863/EU Directive
- 6.7. Cable is REACH compliant per Regulation (EC) No 1907/2006 (224) Updated June 10, 2022
- 6.8. Operating Voltage: 300V RMS
- 6.9. Made in the USA
- 6.10.  **WARNING:** This product may contain chemicals, such as Vinyl Chloride, known to the state of California to cause cancer. For more information, go to www.P65Warnings.ca.gov. Wash hands after handling

**ALL SPECIFIED PARAMETERS WITHOUT A TOLERANCE ARE NOMINAL AND SUBJECT TO VERIFICATION.
BEST WIRE IS NOT RESPONSIBLE FOR UNKNOWN PERFORMANCE ATTRIBUTES THAT WERE NOT MADE
KNOWN TO BEST WIRE AT THE TIME OF DESIGN.**

GET WIRED

